


Adapters



Female NPT Threads			Male NPT Threads							
P-NPT Size	Px-NPT Size	Basic Ordering Number	Dimension, mm					Working Pressure psig (bar)		
			L	F	B	Bx	E	316 SS, Steel	Brass	
1/8	1/16	-FMP-NT2-NT1	27.7	14.3	10.4	9.7	3.0	6500 (447)	3200 (220)	
1/8	1/8	-FMP-NT2	27.9	14.3	10.4	9.7	4.8	6500 (447)	3200 (220)	
1/4	1/16	-FMP-NT4-NT1	30.5	19.1	15.0	9.7	3.0	6600 (454)	3300 (227)	
1/4	1/8	-FMP-NT4-NT2	32.0	19.1	15.0	9.7	4.8	6600 (454)	3300 (227)	
1/4	1/4	-FMP-NT4	35.6	19.1	15.0	14.2	7.1	6600 (454)	3300 (227)	
3/8	1/16	-FMP-NT6-NT1	31.8	22.2	15.0	9.7	3.0	5300 (365)	2600 (179)	
3/8	1/8	-FMP-NT6-NT2	33.8	22.2	15.0	9.7	4.8	5300 (365)	2600 (179)	
3/8	1/4	-FMP-NT6-NT4	38.1	22.2	15.0	14.2	7.1	5300 (365)	2600 (179)	
3/8	3/8	-FMP-NT6	38.4	22.2	15.0	14.2	9.6	5300 (365)	2600 (179)	
1/2	1/8	-FMP-NT8-NT2	40.1	27.0	19.8	9.7	4.8	4900 (337)	2400 (165)	
1/2	1/4	-FMP-NT8-NT4	44.7	27.0	19.8	14.2	7.1	4900 (337)	2400 (165)	
1/2	3/8	-FMP-NT8-NT6	44.4	27.0	19.8	14.2	9.6	4900 (337)	2400 (165)	
1/2	1/2	-FMP-NT8	49.3	27.0	19.8	19.1	11.9	4900 (337)	2400 (165)	
3/4	1/8	-FMP-NT12-NT2	39.6	33.3	20.6	9.7	4.8	4600 (316)	2300 (158)	
3/4	1/4	-FMP-NT12-NT4	47.0	33.3	20.6	14.2	7.1	4600 (316)	2300 (158)	
3/4	3/8	-FMP-NT12-NT6	46.2	33.3	20.6	14.2	9.6	4600 (316)	2300 (158)	
3/4	1/2	-FMP-NT12-NT8	51.3	33.3	20.6	19.1	11.9	4600 (316)	2300 (158)	
3/4	3/4	-FMP-NT12	51.3	33.3	20.6	19.1	15.7	4600 (316)	2300 (158)	
1	1/8	-FMP-NT16-NT2	46.0	41.3	25.4	9.7	4.8	4400 (303)	2200 (151)	
1	1/4	-FMP-NT16-NT4	49.8	41.3	25.4	14.2	7.1	4400 (303)	2200 (151)	
1	3/8	-FMP-NT16-NT6	50.8	41.3	25.4	14.2	9.6	4400 (303)	2200 (151)	
1	1/2	-FMP-NT16-NT8	54.9	41.3	25.4	19.1	11.9	4400 (303)	2200 (151)	
1	3/4	-FMP-NT16-NT12	55.1	41.3	25.4	19.1	15.7	4400 (303)	2200 (151)	
1	1	-FMP-NT16	57.9	41.3	25.4	23.9	22.4	4400 (303)	2200 (151)	
1 1/4	1	-FMP-NT20-NT16	62.7	54.0	25.4	23.9	22.4	5000 (344)	2500 (172)	