


Close Nipples



Male NPT Threads						
P-NPT Size	Basic Ordering Number	Dimension, mm			Working Pressure psig (bar)	
		L	D	E	316 SS, Steel	Brass
1/16	-CNP-NT1	19.1	7.9	3.0	11000 (757)	5500 (378)
1/8	-CNP-NT2	19.1	10.3	4.8	10000 (689)	5000 (344)
1/4	-CNP-NT4	28.4	13.7	7.1	8000 (551)	4000 (275)
3/8	-CNP-NT6	28.4	17.1	9.6	7800 (537)	3900 (268)
1/2	-CNP-NT8	38.1	21.3	11.9	7700 (530)	3800 (261)
3/4	-CNP-NT12	38.1	26.7	15.7	7300 (502)	3600 (248)
1	-CNP-NT16	47.8	33.4	22.4	5300 (365)	2600 (179)

Male ISO Tapered Threads						
P-RT Size	Basic Ordering Number	Dimension, mm			Working Pressure psig (bar)	
		L	D	E	316 SS, Steel	Brass
1/16	-CNP-RT1	19.1	7.9	3.0	11000 (757)	5500 (378)
1/8	-CNP-RT2	19.1	10.3	4.8	10000 (689)	5000 (344)
1/4	-CNP-RT4	28.4	13.7	7.1	8000 (551)	4000 (275)
3/8	-CNP-RT6	28.4	17.1	9.7	7800 (537)	3900 (268)
1/2	-CNP-RT8	38.1	21.3	11.9	7700 (530)	3800 (261)
3/4	-CNP-RT12	38.1	26.7	15.7	7300 (502)	3600 (248)
1	-CNP-RT16	47.8	33.4	22.4	5300 (365)	2600 (179)