


20122


Male NPTF Pipe - Rigid



# Part Number	Thread inch	Hose I.D. inch	A		H inch	J inch	B		Additional Material Brass (B)
			inch	mm			inch	mm	
20122-2-4	1/8x27	3/16	1.72	44	7/16	5/8	0.94	24	
20122-4-4	1/4x18	3/16	1.92	49	9/16	5/8	1.92	29	•
20122-4-5	1/4x18	1/4	2.01	51	9/16	11/16	1.18	30	•
20122-4-6	1/4x18	5/16	2.11	54	9/16	13/16	1.19	30	•
20122-6-8	3/8x18	13/32	2.49	63	3/4	15/16	1.40	36	•
20122-12-12	3/4x14	5/8	3.25	83	1-1/16	1-1/4	1.75	44	•

20622

Female JIC 37° - Swivel




# Part Number	 Thread inch		 Hose I.D. inch	A inch mm		 J inch	 W inch	B inch mm		Additional Material Brass (B)
20622-4-4~	1/4	7/16x20	3/16	1.74	44	5/8	9/16	0.96	24	●
20622-5-5~	5/16	1/2x20	1/4	1.91	49	11/16	5/8	1.08	27	●
20622-6-6	3/8	9/16x18	5/16	2.05	52	13/16	11/16	1.13	29	●
20622-8-8~	1/2	3/4x16	13/32	2.55	65	15/16	7/8	1.46	37	●
20622-10-10~	5/8	7/8x14	1/2	2.80	71	1-1/8	1	1.58	40	●
20622-12-12	3/4	1-1/16x12	5/8	3.15	80	1-1/4	1-1/8	1.65	42	●
20622-16-16	1	1-5/16x12	7/8	2.84	72	1-7/16	1-1/2	1.65	42	●
20622-20-20	1-1/4	1-5/8x12	1-1/8	3.00	76	1-3/4	2	1.72	44	●
20622-24-24	1-1/2	1-7/8x12	1-3/8	3.30	84	2	2-1/4	1.93	49	●
20622-32-32	2	2-1/2x12	1-13/16	4.05	103	2-1/2	2-7/8	2.31	59	●
20622-40-40	2-1/2	3x12	2-3/8	4.17	106	3-1/8	3-3/8	2.36	60	●

~These 20622 fittings contain a dual seat that accepts both the JIC (37°) and SAE (45°) male configurations. The -6 and -12 SAE (45°) swivel fittings are shown under part number 20822.

20822

Female SAE 45° - Swivel



# Part Number	 Thread		 Hose I.D.	A		 J	 W	B		Additional Material Brass (B)
	inch		inch	inch	mm	inch	inch	inch	mm	
20822-4-4	1/4	7/16x20	3/16	1.74	44	5/8	9/16	0.96	24	●
20822-5-5	5/16	1/2x20	1/4	1.91	49	11/16	5/8	1.08	27	●
20822-6-6	3/8	5/8x18	5/16	2.08	53	13/16	3/4	1.16	29	●
20822-8-8	1/2	3/4x16	13/32	2.45	62	15/16	7/8	1.36	35	●
20822-10-10	5/8	7/8x14	1/2	2.80	71	1-1/8	1	1.58	40	●
20822-12-12	3/4	1-1/16x14	5/8	3.10	79	1-1/4	1-1/4	1.60	41	●

Notch in nut for SAE (45°) flare.