

SMC

Different Diameter Plug-in “Y”: KQ2X



Applicable tubing O.D. [inch]	Applicable fitting size ød [inch]	Model	Note) øD1	Note) øD2	L1	L2	A	P	M	Q	øO	øN	Effective area [mm ²]		Min. port size	Weight [g]
			Nylon	Urethane												
ø1/8	ø5/32	KQ2X01-03A	7.1	8.2	44.7	18	42.2	7.1	13.3	5.7	6	3.2	3.2	2.7	2.5	2.8
	ø3/16	KQ2X03-05A	8.2	9.1	46.1	18.8	42.6	8.2	13.3	6.2	6	3.2	3.4	2.9	3.5	3.3
	ø1/4	KQ2X03-07A	8.2	11.1	46.8	19	42.2	8.2	13.3	7.2	6	3.2	3.4	2.9	4.1	4
ø3/16	ø1/4	KQ2X05-07A	9.1	11.1	47.1	19.8	42.5	9.1	13.3	7.2	6	3.2	8.4	7	4.6	4.4
ø1/4	ø5/16	KQ2X07-09A	11.1	13.2	51.2	21.3	45.2	11.1	13.3	8.6	8	4	14.4	12.4	6	6.5

Note) $\phi D1$, $\phi D2$ are maximum diameters.

