


# **37° Flare Bulkhead Connector** *For fractional tube*



| CPI™<br>PART NO. | A-LOK®<br>PART NO. | INTER-<br>CHANGES<br>WITH | INCHES       |              |      |      |      |      |     |          |
|------------------|--------------------|---------------------------|--------------|--------------|------|------|------|------|-----|----------|
|                  |                    |                           | FLARE<br>END | TUBE<br>O.D. | A    | D    | C    | L    | B   | W<br>HEX |
| 2-2 XH2BZ        | 2XABC2             | 200-61-2 AN               | 1/8          | 1/8          | 1.91 | 1.65 | 1.23 | 0.97 | .45 | 1/2      |
| 3-3 XH2BZ        | 3XABC3             | 300-61-3 AN               | 3/16         | 3/16         | 1.98 | 1.71 | 1.26 | 1.00 | .48 | 9/16     |
| 4-2 XH2BZ        | 4XABC2             | 200-61-4 AN               | 1/4          | 1/8          | 2.04 | 1.78 | 1.23 | 0.97 | .55 | 5/8      |
| 4-4 XH2BZ        | 4XABC4             | 400-61-4 AN               | 1/4          | 1/4          | 2.12 | 1.83 | 1.31 | 1.02 | .55 | 5/8      |
| 5-5 XH2BZ        | 5XABC5             | 500-61-5 AN               | 5/16         | 5/16         | 2.21 | 1.92 | 1.41 | 1.12 | .55 | 11/16    |
| 4-6 XH2BZ        | 4XABC6             | 600-61-4 AN               | 1/4          | 3/8          | 2.25 | 1.96 | 1.44 | 1.15 | .55 | 3/4      |
| 6-6 XH2BZ        | 6XABC6             | 600-61-6 AN               | 3/8          | 3/8          | 2.25 | 1.96 | 1.44 | 1.15 | .56 | 3/4      |
| 8-8 XH2BZ        | 8XABC8             | 810-61-8 AN               | 1/2          | 1/2          | 2.59 | 2.19 | 1.65 | 1.25 | .66 | 15/16    |
| 10-10 XH2BZ      | 10XABC10           | 1010-61-10 AN             | 5/8          | 5/8          | 2.74 | 2.34 | 1.68 | 1.28 | .76 | 1-1/16   |
| 12-12 XH2BZ      | 12XABC12           | 1210-61-12 AN             | 3/4          | 3/4          | 3.11 | 2.71 | 1.87 | 1.47 | .86 | 1-3/16   |
| 16-16 XH2BZ      | 16XABC16           | 1610-61-16 AN             | 1            | 1            | 3.65 | 3.16 | 2.27 | 1.78 | .91 | 1-9/16   |

**NOTE:** A and C dimensions are typical finger-tight.

Dimensions for reference only, subject to change.