


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

| | |
|------------------------|---------------------|
| Creation Date: | 17-12-2018 |
| Datasheet No: | DS873W |
| Parker Part No: | 938188Q |
| OEM: | Internormen / Eaton |
| OEM Part No: | 01.E210.10VG.16.S.V |

Product Dimensions

| | | | |
|---------------|-------|---------------|------|
| A (mm) | 70.0 | (inch) | 2.76 |
| C (mm) | 41.0 | (inch) | 1.61 |
| D (mm) | 70.0 | (inch) | 2.76 |
| E (mm) | 219.0 | (inch) | 8.62 |



Construction Materials

| | |
|--------------------------------|--|
| Seal(s): | FPM: Fluoroelastomer |
| Top Endcap: | Mild steel tin plated |
| Bottom Endcap: | Mild steel tin plated |
| Inner Support Cylinder: | Mild steel tin plated |
| Filter Media: | Multilayer fibreglass with coated mesh on both sides |

Calculated Performance Criteria

| | |
|---|--|
| Differential Pressure (Δp): | 0.23 bar @ 150 l/min |
| Tested to ISO3968 @ 32 cSt | 3.31 psi @ 33.00 gpm |
| Efficiency: | >Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater |
| Minimum Collapse Pressure: | >15 bar |
| Tested to ISO2941 | >218 psi |
| Dirt Holding Capacity acc. to ISO16889 | >28.0 gram @ 7 bar terminal pressure drop >28.0 gram @ 102 psi terminal pressure drop |