


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS654W
Parker Part No:	938256Q
OEM:	Hydac
OEM Part No:	0030R020BN4HC

Product Dimensions

A (mm)	35.0	(inch)	1.38
C (mm)	12.2	(inch)	0.48
D (mm)	35.0	(inch)	1.38
E (mm)	105.0	(inch)	4.13
G (mm)	17.9	(inch)	0.70
H (mm)	10.0	(inch)	0.39



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Glass reinforced nylon
Bottom Endcap:	Glass reinforced nylon
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.24 bar @ 20 l/min
Tested to ISO3968 @ 32 cSt	3.48 psi @ 4.40 gpm
Efficiency:	>Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	2.0 gram @ 4 bar terminal pressure drop 2.0 gram @ 58 psi terminal pressure drop