

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS1549W
Parker Part No:	940151Q
OEM:	Internormen / Eaton
OEM Part No:	01.E60.10VG.HR.E.P

Product Dimensions

A (mm)	44.5	(inch)	1.75
B (mm)	22.1	(inch)	0.87
D (mm)	44.5	(inch)	1.75
E (mm)	108.0	(inch)	4.25



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	bar @ l/min
Tested to ISO3968 @ 32 cSt	psi @ gpm
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>210 bar
Tested to ISO2941	>3046 psi
Dirt Holding Capacity acc. to ISO16889	>8.8 gram @ 5 bar terminal pressure drop >8.8 gram @ 73 psi terminal pressure drop