

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS567W
Parker Part No:	PR3153Q
OEM:	Hydac
OEM Part No:	0240D010BH3HC

Product Dimensions

A (mm)	69.0	(inch)	2.72
B (mm)	34.2	(inch)	1.35
D (mm)	69.0	(inch)	2.72
E (mm)	172.0	(inch)	6.77



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Steel tin plated
Bottom Endcap:	Steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on the inflow side and stainless steel mesh on the outlet side

Calculated Performance Criteria

Differential Pressure (Δp):	0.12 bar @ 60 l/min
Tested to ISO3968 @ 32 cSt	1.74 psi @ 13.20 gpm
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>210 bar
Tested to ISO2941	>3046 psi
Dirt Holding Capacity acc. to ISO16889	15.7 gram @ 7 bar terminal pressure drop 15.7 gram @ 102 psi terminal pressure drop