

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS959W
Parker Part No:	PR4471
OEM:	Argo
OEM Part No:	V3.0607-06

Product Dimensions

A (mm)	55.4	(inch)	2.18
B (mm)	28.3	(inch)	1.11
D (mm)	55.4	(inch)	2.18
E (mm)	69.0	(inch)	2.72



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.37 bar @ 75 l/min
Tested to ISO3968 @ 32 cSt	5.37 psi @ 16.50 gpm
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	>8.5 gram @ 7 bar terminal pressure drop >8.5 gram @ 102 psi terminal pressure drop