

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS103W
Parker Part No:	933220Q
OEM:	Pall
OEM Part No:	HC8900FKS26H&Z

Product Dimensions

A (mm)	96.0	(inch)	3.78
B (mm)	56.5	(inch)	2.22
D (mm)	96.0	(inch)	3.78
E (mm)	652.0	(inch)	25.67



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Glass reinforced nylon or mil
Bottom Endcap:	Glass reinforced nylon or mil
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.23 bar @ 570 l/min
Tested to ISO3968 @ 32 cSt	3.34 psi @ 125.38 gp
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	>183.0 gram @ 7 bar terminal pressure drop >183.0 gram @ 102 psi terminal pressure drop