

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS465W
Parker Part No:	938358Q
OEM:	MP Filtri
OEM Part No:	HP3202A06VN&AN

Product Dimensions

A (mm)	78.0	(inch)	3.07
B (mm)	40.5	(inch)	1.59
D (mm)	78.0	(inch)	3.07
E (mm)	235.0	(inch)	9.25



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	1.10 bar @ 350 l/min
Tested to ISO3968 @ 32 cSt	15.95 psi @ 76.99 gp
Efficiency:	>Beta 200 @ 6 microns & greater >Beta 1000 @ 7 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	51.8 gram @ 5 bar terminal pressure drop 51.8 gram @ 73 psi terminal pressure drop