

## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

<b>Creation Date:</b>	17-12-2018
<b>Datasheet No:</b>	DS1561W
<b>Parker Part No:</b>	940030Q
<b>OEM:</b>	Mahle
<b>OEM Part No:</b>	PI8330DRG40

### Product Dimensions

<b>A (mm)</b>	83.5	<b>(inch)</b>	3.29
<b>B (mm)</b>	47.4	<b>(inch)</b>	1.87
<b>D (mm)</b>	83.5	<b>(inch)</b>	3.29
<b>E (mm)</b>	255.0	<b>(inch)</b>	10.04



### Construction Materials

<b>Seal(s):</b>	FPM: Fluoroelastomer
<b>Top Endcap:</b>	Mild steel tin plated
<b>Bottom Endcap:</b>	Mild steel tin plated
<b>Inner Support Cylinder:</b>	Mild steel tin plated
<b>Filter Media:</b>	Single layer stainless steel mesh with stainless steel support mesh on the outlet side

### Calculated Performance Criteria

<b>Differential Pressure (<math>\Delta p</math>):</b>	bar @ l/min
<b>Tested to ISO3968 @ 32 cSt</b>	psi @ gpm
<b>Efficiency:</b>	>Beta 200 @ 40 (nominal) microns & great >Beta 1000 @ microns & greater
<b>Minimum Collapse Pressure:</b>	>30 bar
<b>Tested to ISO2941</b>	>435 psi
<b>Dirt Holding Capacity acc. to ISO16889</b>	