

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS1069W
Parker Part No:	943631Q
OEM:	MP Filtri
OEM Part No:	HP1352A10VH&AH

Product Dimensions

A (mm)	51.0	(inch)	2.01
B (mm)	27.1	(inch)	1.07
D (mm)	51.0	(inch)	2.01
E (mm)	234.0	(inch)	9.21



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Steel tin plated
Bottom Endcap:	Steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on the inflow side and stainless steel mesh on the outlet side

Calculated Performance Criteria

Differential Pressure (Δp):	0.44 bar @ 200 l/min
Tested to ISO3968 @ 32 cSt	6.38 psi @ 43.99 gpm
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>210 bar
Tested to ISO2941	>3046 psi
Dirt Holding Capacity acc. to ISO16889	>23.0 gram @ 7 bar terminal pressure drop >23.0 gram @ 102 psi terminal pressure drop