


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS997W
Parker Part No:	943928Q
OEM:	MP Filtri
OEM Part No:	MR2504A10V&A

Product Dimensions

A (mm)	106.0	(inch)	4.17
B (mm)	72.0	(inch)	2.83
C (mm)	10.2	(inch)	0.40
D (mm)	106.0	(inch)	4.17
E (mm)	465.0	(inch)	18.31



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Outer Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.36 bar @ 600 l/min
Tested to ISO3968 @ 32 cSt	5.22 psi @ 131.98 gp
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>10 bar
Tested to ISO2941	>145 psi
Dirt Holding Capacity acc. to ISO16889	>55.4 gram @ 4 bar terminal pressure drop >55.4 gram @ 58 psi terminal pressure drop