


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS991W
Parker Part No:	943952Q
OEM:	MP Filtri
OEM Part No:	MR6303A10V&A

Product Dimensions

A (mm)	126.0	(inch)	4.96
B (mm)	92.0	(inch)	3.62
C (mm)	10.2	(inch)	0.40
D (mm)	126.0	(inch)	4.96
E (mm)	390.0	(inch)	15.35



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Outer Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.35 bar @ 600 l/min
Tested to ISO3968 @ 32 cSt	5.08 psi @ 131.98 gp
Efficiency:	>Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater
Minimum Collapse Pressure:	>10 bar
Tested to ISO2941	>145 psi
Dirt Holding Capacity acc. to ISO16889	>56.1 gram @ 4 bar terminal pressure drop >56.1 gram @ 58 psi terminal pressure drop