

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS140W
Parker Part No:	PR3440Q
OEM:	Pall
OEM Part No:	HC9600FKT4H&Z

Product Dimensions

A (mm)	80.0	(inch)	3.15
B (mm)	43.2	(inch)	1.70
D (mm)	80.0	(inch)	3.15
E (mm)	116.0	(inch)	4.57



Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Glass reinforced nylon
Bottom Endcap:	Glass reinforced nylon
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (Δp):	0.45 bar @ 140 l/min
Tested to ISO3968 @ 32 cSt	6.53 psi @ 30.80 gpm
Efficiency:	>Beta 200 @ 20 microns & greater >Beta 1000 @ 22 microns & greater
Minimum Collapse Pressure:	>20 bar
Tested to ISO2941	>290 psi
Dirt Holding Capacity acc. to ISO16889	>23.0 gram @ 7 bar terminal pressure drop >23.0 gram @ 102 psi terminal pressure drop