



US Office:
1443 E Gaston St
Lincolnton, NC
28092
USA

CAN Office
188 Industrial Park Cres.
Sault Ste. Marie, ON
P6B 5P2
Canada

Toll Free: 800-465-MAIN(6246)
Phone: 705-945-6429
Fax: 705-949-9431

sales@mainfilter.com
<https://www.mainfilter.com>

Main Filter Technical Data - For pricing and stock, please visit our website.

MF0057995

Part Type: Hydraulic
Filter Type: Spin-On
Media: Cellulose
Seal Material: Buna
Fluid Type: HH / HL / HM / HV
Flow Direction: Outside-In

Dimensions (Inches)

Height: 5.38
O.D. Top: 3.75
I.D. Top:
O.D. Bottom: 3.75
I.D. Bottom:

Rating

Micron 1: 10
Micron 2:
Flow Rate (GPM): 22 GPM
Collapse Pressure (psi): 72
Filter area (sq in):
Beta Ratio 1: 2/10
Beta Ratio 2:
Capacity (gr):
Burst Pressure (psi): 304

Misc. Information

Thread Type: UNF
Weight (lbs): 1.54
By-pass: No
Thread Size (in): 1
Handle: No
Wrap: No
By-Pass Setting (psi):

