



US Office:
1443 E Gaston St
Lincolnton, NC
28092
USA

CAN Office
188 Industrial Park Cres.
Sault Ste. Marie, ON
P6B 5P2
Canada

Toll Free: 800-465-MAIN(6246)
Phone: 705-945-6429
Fax: 705-949-9431

sales@mainfilter.com
<https://www.mainfilter.com>

Main Filter Technical Data - For pricing and stock, please visit our website.

MF0058054

Part Type: Hydraulic
Filter Type: Spin-On
Media: Glass
Seal Material: Buna
Fluid Type: HH / HL / HM / HV
Flow Direction: Outside-In

Dimensions (Inches)

Height: 7.88
O.D. Top: 3.75 **O.D. Bottom:** 3.75
I.D. Top: **I.D. Bottom:**

Rating

Micron 1: 5 **Beta Ratio 1:** 200/5.4
Micron 2: **Beta Ratio 2:** 1000/7.7
Flow Rate (GPM): 26 GPM **Capacity (gr):** 33,50387
Collapse Pressure (psi): 145 **Burst Pressure (psi):** 261
Filter area (sq in): 453

Misc. Information

Thread Type: UNF **Thread Size (in):** 1 1/2
Weight (lbs): 1.9 **Handle:** No **Wrap:** No
By-pass: No **By-Pass Setting (psi):**

