



US Office:
1443 E Gaston St
Lincolnton, NC
28092
USA

CAN Office
188 Industrial Park Cres.
Sault Ste. Marie, ON
P6B 5P2
Canada

Toll Free: 800-465-MAIN(6246)
Phone: 705-945-6429
Fax: 705-949-9431

sales@mainfilter.com
<https://www.mainfilter.com>

Main Filter Technical Data - For pricing and stock, please visit our website.

MF0058063

Part Type: Hydraulic
Filter Type: Spin-On
Media: Glass
Seal Material: Buna
Fluid Type: HH / HL / HM / HV
Flow Direction: Outside-In

Dimensions (Inches)

Height: 6.94
O.D. Top: 5.06
I.D. Top: 5.06
O.D. Bottom: 5.06
I.D. Bottom: 5.06

Rating

Micron 1: 25
Micron 2: 25
Flow Rate (GPM): 40 GPM
Collapse Pressure (psi): 145
Filter area (sq in): 145
Beta Ratio 1: 200/20.7
Beta Ratio 2: 1000/26.6
Capacity (gr): 261
Burst Pressure (psi): 261

Misc. Information

Thread Type: UNF
Weight (lbs): 2.5
By-pass: No
Thread Size (in): 1 1/2
Handle: No
Wrap: No
By-Pass Setting (psi):

