



US Office:
1443 E Gaston St
Lincolnton, NC
28092
USA

CAN Office
188 Industrial Park Cres.
Sault Ste. Marie, ON
P6B 5P2
Canada

Toll Free: 800-465-MAIN(6246)
Phone: 705-945-6429
Fax: 705-949-9431

sales@mainfilter.com
<https://www.mainfilter.com>

Main Filter Technical Data - For pricing and stock, please visit our website.

MF0058320

Part Type: Hydraulic
Filter Type: Coreless
Media: Glass
Seal Material: Viton
Fluid Type: HH / HL / HM / HV
Flow Direction: Outside-In

Dimensions (Inches)

Height:	36.50		
O.D. Top:	5.98	O.D. Bottom:	5.98
I.D. Top:	3.78	I.D. Bottom:	3.88

Rating

Micron 1:	3	Beta Ratio 1:	200/3
Micron 2:		Beta Ratio 2:	1000/4.5
Flow Rate (GPM):		Capacity (gr):	88.41076
Collapse Pressure (psi):	145	Burst Pressure (psi):	
Filter area (sq in):	1195		

Misc. Information

Thread Type:		Thread Size (in):	
Weight (lbs):	8.053	Handle:	Yes
By-pass:	No	Wrap:	No
		By-Pass Setting (psi):	

