



US Office:
1443 E Gaston St
Lincolnton, NC
28092
USA

CAN Office
188 Industrial Park Cres.
Sault Ste. Marie, ON
P6B 5P2
Canada


Toll Free: 800-465-MAIN(6246)
Phone: 705-945-6429
Fax: 705-949-9431

sales@mainfilter.com
<https://www.mainfilter.com>

Main Filter Technical Data - For pricing and stock, please visit our website.

MF0058322

Part Type:	Hydraulic		
Filter Type:	Coreless		
Media:	Glass		
Seal Material:	Viton		
Fluid Type:	HH / HL / HM / HV		
Flow Direction:	Outside-In		
Dimensions (Inches)			
Height:	36.50		
O.D. Top:	5.98	O.D. Bottom:	5.98
I.D. Top:	3.78	I.D. Bottom:	3.88
Rating			
Micron 1:	5	Beta Ratio 1:	200/5,4
Micron 2:		Beta Ratio 2:	1000/7.7
Flow Rate (GPM):		Capacity (gr):	111.947138
Collapse Pressure (psi):	145	Burst Pressure (psi):	
Filter area (sq in):	1195		



Misc. Information

Thread Type:		Thread Size (in):	
Weight (lbs):	8.053	Handle:	Yes
By-pass:	No	Wrap:	No
		By-Pass Setting (psi):	