



US Office:
1443 E Gaston St
Lincolnton, NC
28092
USA

CAN Office
188 Industrial Park Cres.
Sault Ste. Marie, ON
P6B 5P2
Canada

Toll Free: 800-465-MAIN(6246)
Phone: 705-945-6429
Fax: 705-949-9431

sales@mainfilter.com
<https://www.mainfilter.com>

Main Filter Technical Data - For pricing and stock, please visit our website.

MF0063902

Part Type: Hydraulic
Filter Type: Return Line
Media: Stainless Steel Fiber
Seal Material: Viton
Fluid Type: HH / HL / HM / HV
Flow Direction: Outside-In

Dimensions (Inches)

Height: 19.02
O.D. Top: 4.90
I.D. Top:
O.D. Bottom: 4.90
I.D. Bottom: 3.80

Rating

Micron 1: 5
Micron 2:
Flow Rate (GPM):
Collapse Pressure (psi): 435
Filter area (sq in): 1328
Beta Ratio 1: 200/5
Beta Ratio 2:
Capacity (gr): 34,51695
Burst Pressure (psi):

Misc. Information

Thread Type:
Weight (lbs): 7.3
By-pass: Yes
Thread Size (in):
Handle:
Wrap:
By-Pass Setting (psi): 43.5

