

# ▶ MV HEPA SERIES PLASTIC FRAME 292 mm

EPA, HEPA & ULPA FILTERS ◀

<b>Media</b>	Microglass Fiber
<b>Frame</b>	Plastic (PS)
<b>Final Pressure Drop</b>	600 Pa
<b>Operating Temperature</b>	80°C
<b>Filter Efficiency****</b>	E10-H13
<b>Gasket</b>	Flat Neoprene or Half Round Endless Polyurethane
<b>Protection Grids</b>	Optional
<b>Separators</b>	Hotmelt



## Applications

- Air conditioning systems (Hospitals, Laboratories, Museums)
- Industrial processes (Pharmaceutical, Food, Microelectronics)

## Advantages

- Incinerable
- Rigid frame
- MV product line fully meets the requirements for VDI 6022

Part Number	Filter Class EN 1822	Dimensions			Media Area (m <sup>2</sup> )	Air Flow (m <sup>3</sup> /h)	Pressure Drop (Pa)
		Width (mm)	Length (mm)	Depth (mm)			

### ▶ E10

MV-H10-01	E10	292	592	292	8,5	1700	170
MV-H10-02	E10	492	592	292	15,0	2800	170
MV-H10-03	E10	592	592	292	18,0	3400	170

### ▶ E11

MV-H11-01	E11	292	592	292	8,5	1700	200
MV-H11-02	E11	492	592	292	15,0	2800	200
MV-H11-03	E11	592	592	292	18,0	3400	200

### ▶ E12

MV-H12-01	E11	292	592	292	8,5	1250	240
MV-H12-02	E12	492	592	292	15,0	2100	240
MV-H12-03	E12	592	592	292	18,0	2500	240

### ▶ H13

MV-H13-01	H13	292	592	292	8,5	1250	280
MV-H13-02	H13	492	592	292	15,0	2100	280
MV-H13-03	H13	592	592	292	18,0	2500	280

\*\*\*\* According to EN 1822